

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____ User's weight Kg _____

Key
☐ standard
☐ option

PAGE 1/2
 May 2024

Dealer _____

L Seat width ☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48 ☐ 50
☐ 52* ☐ 56* ☐ 60 (including cover for footplate according to setup)

P Seat depth ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46
 Adjustable up to 6 cm (max.50cm) ☐ 48 ☐ 50

HS Back-rest height ☐ 29 ☐ 31 ☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45
☐ 47 ☐ 49 ☐ 51 ☐ 55 ☐ 60

HA Front seat/floor height (with MAX size of front castors) ☐ 38_(fc80max) ☐ 39_(fc100max) ☐ 40_(fc125max) ☐ 42_(fc150max) ☐ 45_(fc175max)
 (NOTE: 175 front castors do not allow 82° detachable footrests) ☐ 44_(fc150max) ☐ 46_(fc175max)


HP Rear seat/floor height ☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 45 ☐ 46 ☐ 48
 NOTE: 24" rear wheels (if HP min.38/max 48) 22" (if HP min.36/max 45) 20" (if HP min.34/max 43)

DP Foot-rest/seat distance ☐ 34 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45
 (from 17 to 32 cm footrest directly assembled on the frame)

cm

ALTHEA19.M

**LOWERED set up
& DAMPENED backrest**
 alum.foldable frame




Dampened backrest uses gas springs to compensate for rapid involuntary body movements.

Frame colour
☐ Matte black
☐ Metallic blue ☐ Pearl red ☐ Metallic grey
☐ Orange ☐ Emerald green ☐
 (see "Colours" catalogue)
☐ Neon orange ☐ Neon green


1 Upholstery
☐ Tension adj. nylon backrest upholstery
☐ Tension adj. breath.backr.
☐ Without any back-rest upholstery
☐ With divided seat (joint by velcro, def.)
☐ With one entire seat (not depth adjustable)

2 Upholstery colour
 (Coloured uphol. only with Tension. adj. nylon)
☐ Black
☐ Red★ ☐ Orange★
☐ Light blue★ ☐ Green★
☐ Cornflower blue★


☐ **Not Detachable foot-rest**
☐ **Dampened not det. foot-rest**
 (needs single dampened footplate with fastening block)




☐ **Detachable foot-rest 82° angle**
 (DP 41 cm)
 (82° footrests do not allow any 175 front castors)




☐ **Detachable foot-rest 68° angle**
 (DP 41 cm)




☐ **Dampened det. foot-rest 68° angle**
 (needs single dampened footplate with fastening block)



☐ **Elevating foot-rest (detachable)**




☐ **Plastic separate**




☐ Cover f/footplates *
☐ Foot-holding belts (L50max)
☐ Heel stops (L50max)
 (* eventually included f/L 52 to 60)

Single aluminium profile tilt adj.footplate:
 (not available with elevating footrest)




☐ Foot-holding belts

Separate aluminium profile tilt adjustable footplates:




Single DAMPENED footplate
 aluminium profile, w/fastening block
 (needed in case of dampened footrest)

☐ forward
☐ backward



☐ Foot-holding belts

☐ **Detachable Desk armrest h 22 cm**




☐ 27 cm high from the seat

Elbow-rest

☐ Classic (30 cm long)
☐ Straight (26 cm long)
☐ Tubular
☐ Hemiplegic RX
☐ Hemiplegic LX

☐ **Detachable "U" armrest h 22 cm**




☐ 27 cm high from the seat


Elbow-rest

☐ Straight (26 cm long)
☐ Straight (36 cm long)
☐ Tubular
☐ Hemiplegic RX
☐ Hemiplegic LX

Height adjustable detachable armrest
 (only closed)



☐ Desk model



☐ "U" model

Elbow-rest

☐ Classic (30 cm long)
☐ Classic (36 cm long)
☐ Straight (26 cm long)
☐ Straight (36 cm long)
☐ Hemiplegic RX
☐ Hemiplegic LX

☐ Order N° _____ ☐ Quotation
Date _____ Signature _____
Customer Ref. _____

PAGE 2/2
May 2024

ALTHEA19.M LOWERED set up
& DAMPENED backrest

Dealer _____

Rear wheels

- ☐ 24" 36 spokes ☐ 12" solid*
☐ 22" 36 spokes ☐ 12" pneumatic*
☐ 20" 36 spokes (N.A. if HP=42 or HP≥ 46
if HP44: only curved rear frame)
☐ 24" MTB citybike tyre
☐ 24" MTB offroad tyre
☐ 24" Light (24 spokes)

- ☐ Pneum. Plugged (x 1"3/8) **Tyres**
Pneum. high press. ☐ Plugged ☐ Smooth
☐ Solid x 1" 3/8
☐ Solid KIK 24"
☐ 24"/22" Pneum. Marathon Plus

Pushrims

- ☐ Aluminium silver
☐ Chromium-plated steel 24"
☐ Aluminium dark
☐ Rubber coated
☐ OVAAL al.silver (*)
☐ OVAALS al.dark (*)
☐ OVAALG al.dark w/sil. insert (*)
☐ Carbolife CURVE L 24"(*)
☐ Carbolife GEKKO 24" (*)
☐ Silicon covers 24"
(*) not available with MTB wheels

Spoke guards



- ☐ Transparent
☐ Black
☐ Fantasy
code pattern:
(see catalogue of spokeguards)

Front castors

- ☐ 100 (4"x1.1/4) solid - plastic rim
☐ 100 (4"x1.1/4) solid - alum. rim
☐ 125 (5"x1.1/4) solid - plastic rim
☐ 125 (5"x1.1/4) solid - alum. rim
☐ 150 (6") pneumatic
☐ 150 (6") solid
☐ 175 (7") solid
☐ 175 (7") pneumatic

Straight Rear Frame

- ☐ With small wheels for narrow passages (default) ☐ Without any small wheels for narrow passages




Unbalancing system

- ☐ Right
☐ Left
(Only with straight rear frame)

Anti-tip device

- ☐ Right
☐ Left
(Only with straight rear frame)

CURVED Rear Frame Unbalancing system




- ☐ Right
☐ Left
(Only with curved rear frame)

Revolving anti-tip device

- ☐ Right
☐ Left
(Only with curved rear frame)

Single drive

- (only with 24" or 22" rear wheels)
☐ Right
☐ Left




Push handles

- ☐ Standard ☐ Height adjustable
(max L = 48 cm)
(Compulsory with HP44cm or lower)




Centre of gravity (COG)

- ☐ -2 cm (extended plate)
☐ 3,5 cm
☐ 5,5 cm
☐ 7,5 cm
(Measurements consider HP=44 cm)



Lateral Supports, swing away


- ☐ Right
☐ Left



Specify the height "h"
from the center of the
swing away to the seat

Head-rest

Padded




- ☐ Fixed
☐ Height adjustable

Orbital


- ☐ Anatomic



- ☐ Moulded



- ☐ With lateral supports




Specify "h" & "d" where requested
Standard: h = 20 cm d = 15 cm

h = ... cm d = ... cm

Table


- ☐ Transparent
☐ RxOLx Hemiplegic transp.
☐ Plastic grey
☐ Soft padded

- Specify the fastening:
☐ single ☐ double



(Only with arm-rest) OXL if L>50cm

Lined cushion in foam polyurethane



- ☐ 3 cm high
☐ 5 cm high


Brakes

- ☐ Classic - short handle
☐ Classic - long handle
☐ Drum
☐ Right single brake
☐ Left single brake
☐ Drum+classic

Options

- 25 ☐ "M" velcro strip (hook) on seat
26 ☐ "M" velcro for Vicair
27 ☐ "F" velcro strip (loop) on seat
28 ☐ Seat/back-rest connection flap
29 ☐ Chest harness
30 ☐ Chest belt
31 ☐ Abductor belt
32 ☐ Front protective covers
33 ☐ Stretched bar
34 ☐ Catheter holder pocket

Abductor



- ☐ 1 ☐ 3 ☐ 5 ☐ 7 cm
☐ cm

Choose or specify the height from seat upholstery

- 35 ☐ R ☐ L Crutch hold./single
36 ☐ R ☐ L Crutch hold./double
37 ☐ Pump for pneumatics
38 ☐ Suitcase holder
39 ☐ 45° pelvic belt
40 ☐ 45° padded pelvic belt
41 ☐ Black backpack
42 ☐ IV bar + poles
43 ☐ IV poles
44 ☐ Q.rel.axles Ø12mm w/42mm bushes (def.)
45 ☐ Q.rel.a. Ø1/2" (12,7mm) w/42mm bushes
46 ☐ Q.rel.a. Ø1/2" (12,7mm) w/50mm bushes