

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____ User's weight Kg _____

PAG. 1/2
 Oct.2026

Dealer _____

Key


☐ standard

☐ option

L Seat width	☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44** ☐ 46** ☐ 48** ☐ 50** (** included compulsory double crossbar)
P Seat depth	☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48** ☐ 50** (** included compulsory double crossbar)
HS Back-rest height	☐ 29 ☐ 31 ☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45 ☐ 47 ☐ 49 (included stretched bar)
HA Front seat/floor height	☐ 42 ☐ 43 ☐ 44 ☐ 46 ☐ 48 ☐ 50 ☐ 52 ☐ 54
HP Rear seat/floor height	☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48 ☐ 50
DP Foot-rest/seat distance	☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45 ☐ 47 ☐ 49 ☐ 51 cm

DIVA

Alum. foldable frame
 crash tested



Frame colour

- ☐ Glossy black ☐ Pearl red ☐ Matte black
☐ Pearl white ☐ Metallic blue ☐ Metallic grey
☐ Basic colours
☐ Special colours
 (see "Colours" catalogue)

①

Backrest upholstery

- ☐ Tension adjustable nylon back-rest
☐ Tens.adjustable breathable backrest
☐ Without any backrest upholstery
☐ **AMEKH** custom postural backrest
 (fill up the proper order form)

②


Upholstery colour

- (Nylon only)
☐ Black
☐ Red ☐ Orange
☐ Light blue ☐ Green
☐ Cornflower blue

③


☐ Not Detachable foot-rest

(with DP=43 cm and P=40 cm)
 (standard)




☐ Not detachable foot-rest

(with DP=43 cm and P=40 cm)




Detachable foot-rest:



☐ Elevating foot-rest (detachable)

☐ Plastic separate

(only DP > 35 cm and W= from 38 to 46 cm)




- ☐ Foot-holding belts
☐ Heel stops

④

Separate aluminium profile tilt adjustable footplates:

- ☐ forward ☐ backward




- ☐ Foot-holding belts


⑤

Single aluminium profile tilt adjustable footplate:

(not available with detachable foot-rests)



- ☐ Up & outward




- ☐ Foot-holding belts

⑥

☐ Closed carbon single footplate

(Note: it might interfere with DP)
 (max W 48cm)




- ☐ Foot-holding belts
☐ Heel stops

⑦

☐ AUTOMATIC closure footplate in carbon

(up to W46)
 for W 48cm
 (Note: it might interfere with DP)
 (max W 48cm)




- ☐ Foot-holding belts

⑧

Height adjustable tip-up armrest

(only closed)
 (minimum height 26cm)
 (minimum depth P36cm)



- ☐ Desk model

- ☐ Sport model

- ☐ "U" model

Elbow-rest

- ☐ Classic (30 cm long)
☐ Straight (26 cm long)
☐ Classic (36 cm long)
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi modular armrest ord.form

⑨


Side-guards

- ☐ Plastic (**)
☐ Aluminium
 (same colour of frame)
☐ Carbon fibre(**)

- ☐ (**) with DIVA on the sideguard support & on seat pocket
☐ (**) without any Diva name

☐ Tip-up detachable Desk armrest h 22 cm

(open with sideguards)



- ☐ 27 cm high from the seat


Elbow-rest

- ☐ Classic (23 cm long)
☐ Straight (26 cm long)
☐ Tubular
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi modular armrest ord.form

☐ Tip-up height adjustable from 22 to 28 cm "L" armrest

(detachable, open with sideguards)




Elbow-rest

- ☐ Tubular
☐ Straight (26 cm long)
☐ Classic (23 cm long)
☐ Classic (30 cm long)

☐ Tip-up detachable Sport armrest h 22 cm

(open with sideguards)



Elbow-rest

- ☐ Straight (26 cm long)
☐ Classic (23 cm long)
☐ Tubular
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi mod.armrest ord.form

⑩

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____

PAG. 2/2
 Oct.2026

DIVA

Dealer _____

Rear wheels ⑮

- ☐ 24" (36 spokes) ☐ 24" Star 6x3(18sp.)
☐ 22" (36 spokes) ☐ 24" Light (24 spokes)
☐ 20" (36 spokes)
☐ 24" Mountain-bike with Citybike tyre
☐ 24" Mountain-bike with Offroad tyre
☐ 24" Ultralight (24 spks) black
☐ 24" Spinergy LX

Tyres

- ☐ Pneumatic Marathon Plus
☐ Plugged ☐ Smooth Pnum. high press.
☐ Solid grey 20"/22" (x 1")
☐ Solid black KIK 24"

Pushrims ⑮

- ☐ Aluminium silver
☐ Aluminium dark
☐ Shiny inox steel 24"
☐ Rubber coated
☐ Carbolife CURVE L 24"(*)
☐ OVAAL silver alum. (*)
☐ OVAALS dark alum. (*)
☐ OVAALG dark w/sil. insert (*)
☐ Carbolife GEKKO 24" (*)
☐ Silicon covers 24" (*)
 (*) not available with MTB wheels


Spoke covers ⑮

- ☐ Transparent 24"
☐ Black 24"
☐ Fantasy
 code pattern
 (see catalogue of spokeguards)


Front castors ⑮

- ☐ 100 (4"x1.1/4) solid with plastic rim
☐ 100 (4"x1) solid with lights
☐ 100 (4"x1.1/4) solid silver alum. rim
☐ 100 (4"x1.1/4) solid black alum. rim
☐ 125 (5"x1.1/4) solid with plastic rim
☐ 125 (5"x1.1/4) solid silver alum. rim
☐ 125 (5"x1.1/4) solid black alum. rim
☐ 150 (6") pneumatic
☐ 150 (6") solid
☐ 175 (7") solid
☐ 175 (7") pneumatic

- ☐ STRAIGHT rear frame with small wheels for narrow passages (default)




- ☐ STRAIGHT rear frame with LEVER-activated narrow passage wheels




(Compulsory: rear seat/floor height HP= from 44 to 48 cm)

Rear frame ⑮

- ☐ STRAIGHT rear frame WITHOUT any small wheels f/narrow passages



- ☐ Curved rear frame



(It is not possible to assemble the small wheels for narrow passages)

Rear wheel camber

- ☐ 0° ☐ 1° ☐ 2° ☐ 3°

- ☐ Q.rel.axles Ø12mm w/42mm bushes (def.)
☐ Q.rel.a. Ø1/2" (12,7mm) w/42mm bushes
☐ Q.rel.a. Ø1/2" (12,7mm) w/50mm bushes

Unbalancing system ⑮

- ☐ Right ☐ Right
☐ Left ☐ Left

(Only for curved rear frame)

Anti-tip device

- ☐ Right
☐ Left


Revolving anti-tip device

(Only with curved rear frame)

- ☐ Right
☐ Left


Single drive ⑮

- ☐ Right
☐ Left



(only with 0° camber)


Extended wheel plate ⑮



Push handles ⑮

- ☐ Standard ☐ Hinged back-rest (no stretched bar)

- ☐ Height adjustable




Backrest ⑮

- ☐ Fixed

Tilt adjustable:

- ☐ -4°
☐ -2°
☐ 0 (90°)
☐ 2°
☐ 4°
☐ 6°



Distance between the hub centre and the backrest ⑮

- ☐ 2,5 cm

- ☐ 5 cm (std)

- ☐ 7,5 cm

(with HP=44 cm)





Table ⑮

- ☐ Transparent
☐ RxOLx Hemiplegic transparent
☐ Plastic grey
☐ Soft padded


specify the fastening:
☐ single ☐ double



(Only with arm-rests)

Head-rest ⑮

Backrest extension



- ☐ Fixed
☐ Height adjustable
 Default h = 20 cm d = 15 cm

Orbital


- ☐ Anatomic



- ☐ Moulded



- ☐ With lateral supports



Lined cushion ⑮

in foam polyurethane



- ☐ 3 cm high
☐ 5 cm high

Anodized set ⑮

(Rear wheel rims and hubs, forks)

- ☐ Black

- ☐ Silver

- ☐ Light blue

- ☐ Red

- ☐ Orange

- ☐ Cyclamen light purple

(Only Light wheels)

Brakes ⑮

(To be valued on the base of the total configuration)

- ☐ Classic - short handle
☐ Classic - pull to brake short handle
☐ Classic - long handle
☐ Scissor
☐ Right single drive
☐ Left single drive
☐ Drum
☐ Drum +classic

Options

- 31 ☐ "M+F" velcro on seat
 32 ☐ "M" velcro strip (hook) on seat
 33 ☐ "F" velcro strip (loop) on seat
 34 ☐ Seat/backrest connection flap
 35 ☐ Padded rigid cushion h 5
 36 ☐ Chest harness
 37 ☐ Chest belt
 38 Lateral supports ☐ RX ☐ OLX
 Swing Away h.....

Note

Options

- 39 ☐ Abductor belt
 40 ☐ Catheter holder pocket
 41 ☐ Stretched bar
 42 ☐ Rx ☐ Lx Crutch holder
 43 ☐ Rx ☐ Lx Double Crutch holder
 44 ☐ Pump for pneumatics
 45 ☐ Suitcase holder
 46 ☐ 45° pelvic belt
 47 ☐ 45° padded pelvic belt
 48 ☐ Black backpack
 49 ☐ Front protective covers
 50 ☐ Double cross bar
 51 ☐ Abductor
 h from the seat
 52 ☐ Fittings for car fastening

crash tested