

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____ User's weight Kg _____

PAGE 1/2
 Oct.2026

Dealer _____

Key



☐ standard

☐ option

☐ ALUMINIUM frame ☐ TITANIUM frame

L Seat width ☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44
 P Seat depth ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46
 HS Back-rest height ☐ 27 ☐ 29 ☐ 31 ☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41
 HA Front seat/floor height ☐ 46 ☐ 48 ☐ 50
 HP Rear seat/floor height ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48
 DP Foot-rest/seat distance ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45 ☐ 47 ☐ 49 cm

QPX
 Hybrid frame
 with adjustable axle



Frame colour

①

- ☐ Shiny titanium (ONLY TITANIUM FRAME)
☐ Natural titanium (ONLY TITANIUM FRAME)
☐ Glossy black ☐ Glossy anthracite ☐ Matte black
☐ Basic colours
☐ Special colours
 (see "Colours" catalogue)

Upholstery

②

- ☐ Tension adjustable nylon back-rest
☐ Tens.adjustable breathable backrest
☐ Without any backrest upholstery
☐ **AMEKH** custom postural backrest
 (fill up the proper order form)


Upholstery colour

③

- ☐ Black
☐ Coloured.....
 Available colours:
 NYLON: orange, red, green, cornflower blue, light blue;
 BREATHABLE: red, grey;

☐ Automatic closure
 foot-plate in carbon





④



- ☐ Foot-holding belts

Pushing handles

⑤




- ☐ Without pushing handles ☐ Fixed pushing handles ☐ Height adjustable pushing handles ☐ Foldable pushing handles

**Distance between
 the hub centre and back-rest**

⑥


* standard range 5÷11



- ☐ 9 cm (standard) * ☐ 7 cm *
☐ 5 cm * ☐ 11 cm *
☐ 3 cm ☐ 13 cm

Back-rest tilt


⑦



- ☐ 89°
☐ 91° (standard)
☐ 93°

Front angle

⑧



- ☐ 83° (standard) (A = 18 cm)
☐ 75° (A = 25 cm)

**Rear
 wheel camber**

⑨

- ☐ 1° ☐ 2° ☐ 3° ☐ 4°

- ☐ Quick release axles
 Ø12mm with 42
 cambered bushes (default)
☐ Q.r.a. Ø 1/2" (12,7 mm)
 w/42 camb.bushes
☐ Q.r.a. Ø 1/2" (12,7 mm)
 w/50 camb.bushes

Side guards

⑩




- ☐ Fix with carbon fibre wing ☐ Detachable with carbon wing



- ☐ Fix with straight carbon fibre ☐ Detachable with straight carbon

☐ Height adjustable
 from 22 to 28cm
 "L" arm-rest,
 detachable and tip-up

⑪




Elbow-rest

- ☐ Tubular
☐ Straight (26 cm long)
☐ Classic (23 cm long)
☐ Classic (30 cm long)

Brakes

⑫




- ☐ Composite brake

- ☐ Standard

- ☐ Pull brake

**Revolving
 anti-tip device**

⑬



- ☐ Right

- ☐ Left

Notes

Dealer

Rear wheels

14

- ☐ 24" Ultralight (24 spokes)
- ☐ 24" Light (24 spokes)
- ☐ 24" Star 6x3 (18 spokes, silver or black)
- ☐ 24" (36 spokes)
- ☐ 24" Mountain-bike with Citybike tyre
- ☐ 24" Mountain-bike with Offroad tyre
- ☐ 24" Spinergy LX
spokes colour.....(black def.)
- ☐ 25" Spinergy LX
spokes colour.....(black def.)
- ☐ 25" Light (24 spokes) black

Tyres

- ☐ Pneum. Marathon Plus
- ☐ Pneum. high pressure Smooth
- ☐ Pneum. high pressure Plugged 24"
- ☐ Pn.Schwalbe Right Run 24"
- ☐ Solid black KIK 24"
not available for Ultralight wheels

Pushrim

15

- ☐ Aluminium silver
 - ☐ Aluminium dark
 - ☐ Shiny stainless steel 24"
 - ☐ Rubber coated
 - ☐ Titanium
 - ☐ OVAAL (silver aluminium)
 - ☐ OVAALS (dark aluminium)
 - ☐ OVAALG (w/sil.insert)
 - ☐ CarboLife CURVE L 24" *
 - ☐ CL CurveL TETRAGRIP rubb.c.24" *
 - ☐ CL QUADRO rubber ct.24" *
 - ☐ CarboLife GEKKO 24" *
 - ☐ Silicon covers 24"
- OVAAL/S/G only in size 24"
- Only OVAAL/GEKKO available for Star6x3
- OVAAL & Carbolife not available for MTB

Spoke guards

16

- ☐ Transparent 24"
 - ☐ Black 24"
 - ☐ Fantasy
- code pattern
(see catalogue of spokeguards)

Front castors

17

- ☐ 80 (3'') solid
- ☐ 80 (3'') solid with lights
- ☐ 100 (4''x1.1/4) solid with plastic rim
- ☐ 100 (4''x1) solid with lights
- ☐ 100 (4''x1.1/4) solid with silver alum. rim
- ☐ 100 (4''x1.1/4) solid with black alum. rim
- ☐ 125 (5''x1.1/4) solid with plastic rim
- ☐ 125 (5''x1.1/4) solid with silver alum. rim
- ☐ 125 (5''x1.1/4) solid with black alum. rim
- ☐ 150 (6'') pneumatic
- ☐ 150 (6'') solid

Pockets

18



- ☐ Small under the seat

Anodized set


20

- ☐ Black
☐ Silver
☐ Light blue
☐ Red
☐ Orange
☐ Cyclamen light purple
 (only 24" Light wheels)

Lined cushion

in foam polyurethane


19



- ☐ 3 cm high
- ☐ 5 cm high

Y shaped
front frame

(default)



- Straight front frame

(compulsory for a seat width of 34cm)

21

Options

- 22 ☐ "M+F" velcro strips (hook and loop) on seat
- 23 ☐ "M" velcro strips (hook) on seat
- 24 ☐ "M" velcro strips for VICAIR
- 25 ☐ "F" velcro strips (loop) on seat
- 26 ☐ Chest harness
- 27 ☐ Chest belt
- 28 ☐ Abductor belt
- 29 ☐ Catheter holder pocket
- 30 ☐ Pump for pneumatics
- 31 ☐ 45° pelvic belt
- 32 ☐ 45° padded pelvic belt
- 33 ☐ Black backpack
- 34 ☐ Front protective covers

Notes