

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____ User's weight Kg _____

PAGE 1/2
 May 2024

Dealer

Key


☐ standard

☐ option

☐ **QUASAR ADJ**

L Seat width ☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44
P Seat depth ☐ 36 ☐ 38 ☒ 40 ☐ 42 ☐ 44 ☐ 46
HS Back-rest height ☐ 27 ☐ 29 ☐ 31 ☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41
HA Front seat/floor height ☐ 46 ☐ 48 ☐ 50
HP Rear seat/floor height ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48
DP Foot-rest/seat distance ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45 ☐ 47 ☐ 49 cm

QUASAR^{ADJ} FOR DANCING



Frame colour

①

- ☐ Shiny titanium ☐ Glossy black
☐ Pearl white ☐ Matte black
☐ Natural titanium
☐ (see "Colours" catalogue)
☐ Neon green ☐ Neon orange

Upholstery

②

- Back-rest:**
 Tension adj nylon
 Breathable tension adj
 Without back-rest:
☒ **FAMEKH**
☐ other seating system.....
- Seat:**
☐ Fix (standard, screws)
☐ Tension adj. (velcro)
☐ Carbon fibre

Upholstery colour

③

- ☐ Black
☐ Coloured (nylon).....
 colours: orange, red, green, cornflower, light blue
☐ Coloured (breathable).....
 colours: red, dry green, grey)

Single tubular titanium footplate

④

- ☐ Open ☐ Carbon fibre closed ☐ Tilt adjustable Carbon fibre closed

Push handles

⑤

- ☐ Without pushing handles ☐ Fixed pushing handles ☐ Foldable pushing handles

Distance between the hub centre and back-rest

⑥

- ☐ 9 cm (standard) ☐ 7 cm
☐ 0 cm (biamputated) ☐ 11 cm
☐ 3 cm ☐ 13 cm
☐ 5 cm ☐ cm

Backrest tilt

⑦

- ☐ 89° ☐ 91° (standard) ☐ 93°

Front frame angle

⑧

- ☐ 83° (standard) (A = 16 cm) ☐ 75° (A = 21 cm)

Rear wheel camber

⑨

- ☐ 1° ☐ 2°
☐ 3° ☐ 4°
☐ cm (max 12°)
☐ Quick rel. axles Ø 12 mm (default)
☐ Quick rel. axles Ø 1/2" (12,7 mm)
☐ Cambered bushes length 42 mm (default)
☐ Cambered bushes length 50 mm

Side-guards

⑩

- ☐ Aluminium with carbon fibre wing ☐ Detachable
☐ Aluminium with straight carbon fibre ☐ Detachable

Backrest bar

⑪

- ☐ Standard: P(bar) 7,5cm; H(bar) 19cm; dia 19mm. ☐ Custom: P.....cm; H.....cm;

Brakes

⑫

- ☐ Without any brake ☐ Scissor brake ☐ Composite
☐ Standard ☐ Pull brake

Central revolving anti-tip device (stand.)

⑬

- ☐ Small wheel of anti-tip with lights
☐ Reinforced central antitip
☐ Reinforced central antitip with carbon footplate for 2nd dancer

Notes

☐ Order N° _____ ☐ Quotation
Date _____ Signature _____
Customer Ref. _____

PAGE 2/2
May 2024

QUASAR^{ADJ}
FOR DANCING

Dealer _____

Rear wheels

⑭

- ☐ 24" Ultralight (24 spokes)
☐ 24" Light (24 spokes)
☐ 24" Star 6x3 (18 spokes, silver or black)
☐ 24" Spinergy
spokes colour.....(black stand.)
☐ 25" Spinergy
spokes colour.....(black stand.)
☐ 25" Light (24 spokes) black

Tyres

- ☐ Pneum.Schwalbe One 24"/25"
☐ Pneum. high pressure Smooth
☐ Pn.Schwalbe Right Run 24"
☐ Solid KIK 24" not available for Ultralight wheels

Pushrims

⑮

- ☐ Aluminium silver
☐ Aluminium dark
☐ Chromium-plated steel 24"
☐ Rubber coated
☐ Titanium
☐ CarboLife CURVE L 24" *
☐ CL Curve L TetraGrip 24" *
☐ CL Quadro rubber ctd 24" *
☐ CarboLife GEKKO 24" *
☐ Silicon covers 24"

* CL pushrims: only GEKKO suitable for Star 6x3 wheels


Spokes guards

⑯

- ☐ Transparent 24"
☐ Black 24"
☐ Fantasy
code pattern
(see catalogue of spokeguards)

Lined cushion in foam polyurethan

⑰



- ☐ 3 cm high
☐ 5 cm high


Front castors

⑰

- ☐ 80 (3") solid
☐ 80 (3") solid with lights
☐ 100 (4"x1.1/4) solid with plastic rim
☐ 100 (4"x1) solid with lights
☐ 100 (4"x1.1/4) solid with alum. rim
☐ 125 (5"x1.1/4) solid with plastic rim
☐ 125 (5"x1.1/4) solid with alum. rim
☐ 125 (5"x1) solid with lights
☐ 150 (6") pneumatic
☐ 150 (6") solid

Pockets

⑱



- ☐ Small under the fix seat
(for fix seat by screws)



- ☐ On the back-rest

Anodized set

(Rear wheel rims & hubs if LIGHT 24",
sideguard supports, forks and fittings)

⑳

- ☐ Black
☐ Silver
☐ Light blue
☐ Red
☐ Orange
☐ Cyclamen light purple


(only 24" Light wheels)

Options


- 22 ☐ "M+F" velcro strips (hook and loop) on seat
23 ☐ "M" velcro strips (hook) on seat
24 ☐ "F" velcro strips (loop) on seat

25 ☐ Rigid welded seat
26 ☐ Welded sideguards, in titanium
27 ☐ Pump for pneumatics
28 ☐ 45° pelvic belt
29 ☐ 45° padded pelvic belt
30 ☐ Black backpack
31 ☐ Front protective covers

☐ STANDARD SEAT




☐ "Y" SHAPED FRONT FRAME (stand.)




standard:
L-13cm

- ☐ Custom front opening
.....cm

☐ ERGO SEAT




☐ "V" SHAPED FRONT FRAME



(The tilt adjustable footplate only
is suitable with the V" shaped front frame)

☐ STRAIGHT FRONT FRAME



(Standard front frame for
seat width of 34cm)

㉑