OFFCARR

☐ Order N° _____ ☐ Quotation

Date _____ Signature _____

Customer Ref. _____

PAG. 1/2
May 2024

Dealer

DIVA
Alum. foldable frame

Key	☐ standard	○ option

L	Seat width	☐34 ☐36 ☐38 ☐40 ☐42 ☐44** ☐46**
		○48** ☐50** (** included compulsory double crossbar)
P	Seat depth	☐34 ☐36 ☐38 ☐**40** ☐42 ☐44
		○46 ○48** ○50** (** included compulsory double crossbar)
HS	Back-rest height	☐29 ☐31 ☐33 ☐35 ☐37 ☐39 ☐41
		○43 ○45 ○47 ○49 (included stretched bar)
HA	Front seat/floor height	☐42 ☐43 ☐44 ☐46 ☐48 ☐**50** ☐52
		○54
HP	Rear seat/floor height	☐38 ☐40 ☐42 ☐44 ☐**46** ☐48 ☐50
DP	Foot-rest/seat distance	☐33 ☐35 ☐37 ☐39 ☐41 ☐43 ☐45 ☐47 ☐49 ☐51 cm

Frame colour ①

☐ Glossy black ☐ Pearl red ☐ Matte black
☐ Pearl white ☐ Metallic blue ☐ Metallic grey
○ .... (see "Colours" catalogue)
○ Neon orange ○ Neon green

Backrest upholstery ②

☐ Tension adjustable nylon back-rest
☐ Tens.adjustable breathable backrest
☐ Without any backrest upholstery
○ **SAMEKH** custom postural backrest (fill up the proper order form)

Upholstery colour ③
(nylon only)
☐ Black
○ Red ○ Orange
○ Light blue ○ Green
○ Cornflower blue

☐ **Not Detachable foot-rest** ④
(with DP=43 cm and P=40 cm)
(standard)
84°

☐ **Not detachable foot-rest**
(with DP=43 cm and P=40 cm)
76°

Detachable foot-rest:
○ 84° ○ 76°

○ **Elevating foot-rest (detachable)**

☐ **Plastic separate** ⑤
(only DP > 35 cm and L = from 38 to 46 cm)
○ Foot-holding belts
○ Heel stops

○ **Single closed in carbon fibre** ⑧
○ Foot-holding belts
○ Heel stops

### **Separate aluminium profile tilt adjustable footplates:** ⑥
☐ forward ☐ backward
○ Foot-holding belts

### ○ **Automatic closure footplate in carbon** ⑨
(Not available with detachable or elevating foot-rest
NB: for a seat width of 46cm maximum)
○ Foot-holding belts

Single aluminium profile tilt adjustable footplate: ⑦
(not available with detachable foot-rest)
☐ forward
☐ backward
○ Up & outward
○ Foot-holding belts

Side-guards ⑩
☐ Plastic
☐ Aluminium (same colour)
○ Carbon fibre

☐ **Tip-up detachable Desk armrest h 22 cm** ⑪
(open with sideguards)
☐ 27 cm high from the seat

Elbow-rest
☐ Classic (23 cm long)
☐ Straight (26 cm long)
☐ Tubular
○ Hemiplegic RX
○ Hemiplegic LX
note: see also Hemi modular armrest ord.form

○ **Tip-up height adjustable from 22 to 28 cm "L" armrest** ⑫
(detachable, open with sideguards)
☐ Not detachable

Elbow-rest
☐ Tubular
☐ Straight (26 cm long)
☐ Classic (23 cm long)
☐ Classic (30 cm long)

☐ **Tip-up detachable Sport armrest h 22 cm** ⑬
(open with sideguards)

Elbow-rest
☐ Straight (26 cm long)
☐ Classic (23 cm long)
☐ Tubular
○ Hemiplegic RX
○ Hemiplegic LX
note: see also Hemi mod.armrest ord.form

Height adjustable tip-up armrest (only closed) ⑭
(minimum height 26cm)
(minimum depth P36cm)
○ Desk model
○ Sport model
○ "U" model

Elbow-rest
☐ Classic (30 cm long)
☐ Straight (26 cm long)
○ Classic (36 cm long)
○ Hemiplegic RX
○ Hemiplegic LX
note: see also Hemi modular armrest ord.form

OFFCARR

☐ Order N° _____ ☐ Quotation

Date _____ Signature _____

Customer Ref. _____

PAG. 2/2
May 2024

DIVA

Dealer

Rear wheels ⑮

- ☐ 24" (36 spokes) ☐ 24" Star 6x3 (18sp.)
- ☐ 22" (36 spokes) ☐ 24" Light (24 spokes)
- ☐ 20" (36 spokes)
- ☐ 24" Mountain-bike with Citybike tyre
- ☐ 24" Mountain-bike with Offroad tyre
- ○ 24" Ultralight (24 spks) black
- ○ 24" Spinergy LX

Tyres
- ☐ Pneumatic Marathon Plus
- ☐ Plugged ☐ Smooth Pneum. high press.
- ○ Solid grey 20"/22" (x 1")
- ○ Solid black KIK 24"

Pushrims ⑯

- ☐ Aluminium silver
- ☐ Aluminium dark
- ○ Chromium-plated steel 24"
- ○ Rubber coated
- ○ Carbolife CURVE L 24"(*)
- ○ OVAAL silver alum. (*)
- ○ OVAALS dark alum. (*)
- ○ OVAALG dark w/sil. insert (*)
- ○ Carbolife GEKKO 24" (*)
- ○ Silicon covers 24"
 - (*) not available with MTB wheels

Spoke covers ⑰

- ○ Transparent 24"
- ○ Black 24"
- ○ Fantasy

 code pattern ....

  (see catalogue of spokeguards)

Front castors ⑱

- ☐ 100 (4''x1.1/4) solid with plastic rim
- ○ 100 (4''x1) solid with lights
- ○ 100 (4''x1.1/4) solid with alum. rim
- ☐ 125 (5''x1.1/4) solid with plastic rim
- ☐ 125 (5''x1.1/4) solid with alum. rim
- ○ 125 (5''x1) solid with lights
- ☐ 150 (6'') pneumatic
- ☐ 150 (6'') solid
- ☐ 175 (7'') solid
- ☐ 175 (7'') pneumatic

Rear frame ⑲

- ☐ STRAIGHT rear frame with small wheels for narrow passages (default)

- ☐ STRAIGHT rear frame WITHOUT any small wheels f/narrow passages

- ○ STRAIGHT rear frame with LEVER-activated narrow passage wheels

- ☐ Curved rear frame

(Compulsory: rear seat/floor height HP= from 44 to 48 cm)

(It is not possible to assemble the small wheels for narrow passages)

Rear wheel camber
- ☐ 0° ☐ 1° ☐ 2° ☐ 3°

- ☐ Q.rel.axles Ø12mm w/42mm bushes (def.)
- ☐ Q.rel.a. Ø1/2" (12,7mm) w/42mm bushes
- ☐ Q.rel.a. Ø1/2" (12,7mm) w/50mm bushes

Unbalancing system ⑳

- ☐ Right ☐ Right
- ☐ Left ☐ Left

(Only for curved rear frame)

### Anti-tip device
- ○ Right
- ○ Left

Revolving anti-tip device
(Only with curved rear frame)
- ○ Right
- ○ Left

Single drive ㉑
- ○ Right
- ○ Left

(only with 0° camber)

○ Extended wheel plate ㉒

Push handles ㉓
- ☐ Standard
- ○ Hinged back-rest (no stretched bar)
- ○ Height adjustable

Backrest ㉔
- ☐ Fixed

Tilt adjustable:
- ☐ -4°
- ☐ -2°
- ☐ 0 (90°)
- ☐ 2°
- ☐ 4°
- ☐ 6°

90°

Distance between the hub centre and the backrest ㉕
- ☐ 2,5 cm
- ☐ 5 cm (std)
- ☐ 7,5 cm

(with HP=44 cm)

Table ㉖
- ○ Transparent
- ○ Rx ○ Lx Hemiplegic transparent
- ○ Plastic grey
- ○ Soft padded

specify the fastening:
- ☐ single ☐ double

(Only with arm-rests)

Head-rest ㉗

**Padded**
- ○ Fixed
- ○ Height adjustable

Orbital
- ○ Anatomic
- ○ Moulded
- ○ With lateral supports

Specify "h" & "d" where requested
Standard: h = 20 cm d = 15 cm
h = ... cm d = ... cm

Lined cushion ㉘
iin foam polyirethane

- ○ 3 cm high
- ○ 5 cm high

Anodized set ㉚
(Rear wheel rims and hubs, forks)

- ☐ Black
- ☐ Silver
- ○ Light blue
- ○ Red
- ○ Orange
- ○ Cyclamen light purple

(Only Light wheels)

Brakes ㉙
(To be valued on the base of the total configuration)
- ☐ Classic - short handle
- ○ Classic - pull to brake short handle
- ○ Classic - long handle
- ○ Scissor
- ○ Right single drive
- ○ Left single drive
- ○ Drum
- ○ Drum +classic

Options
- 31 ☐ "M+F" velcro on seat
- 32 ☐ "M" velcro strip (hook) on seat
- 33 ☐ "F" velcro strip (loop) on seat
- 34 ☐ Seat/backrest connection flap
- 35 ○ Padded rigid cushion h 5
- 36 ○ Chest harness
- 37 ○ Chest belt
- 38 Lateral supports ○ RX ○ LX
  Swing Away h..........

Options
- 39 ○ Abductor belt
- 40 ○ Catheter holder pocket
- 41 ○ Stretched bar
- 42 ○ Rx ○ Lx Crutch holder
- 43 ○ Rx ○ Lx Double Crutch holder
- 44 ○ Pump for pneumatics
- 45 ○ Suitcase holder
- 46 ○ 45° pelvic belt
- 47 ○ 45° padded pelvic belt
- 48 ○ Black backpack
- 49 ○ Front protective covers
- 50 ○ Double cross bar
- 51 ○ Abductor
  h .... from the seat
- 52 ○ **Fittings for car fastening** € 190,00

Note
_____
_____
_____