

Dealer

☐ Order N° _____ ☐ Quotation
 Date _____ Signature _____
 Customer Ref. _____ User's weight Kg _____


PAGE 1/2
 May 2024

Key ☐ standard ☐ options

Reclining backrest, 90° to 150°,
 activated by a lever on the pushing
 handles that release gas springs.

RECLINING ALTHEA.R

Alum. foldable frame




- L** Seat width ☐ 34 ☐ 36 ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☐ 46 ☐ 48 ☐ 50
☐ 52 ☐ 56 ☐ 60 (including cover for footplate according to setup)
- P** Seat depth ☐ 36 ☐ 38 ☒ 40 ☐ 42 ☐ 44 ☐ 46
 Adjustable up to 6cm (max.50 cm) ☐ 48 ☐ 50
- HS** Back-rest height ☐ 29 ☐ 31 ☐ 33 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45
☐ 47 ☐ 49 ☐ 51 ☐ 55 ☐ 60
- HA** Front seat/floor height ☐ 42 ☐ 43 ☐ 44 ☐ 46 ☐ 48 ☒ 50 ☐ 52
☐ 54
- HP** Rear seat/floor height ☐ 38 ☐ 40 ☐ 42 ☐ 44 ☒ 46 ☐ 48 ☐ 50
- DP** Foot-rest/seat distance ☐ 34 ☐ 35 ☐ 37 ☐ 39 ☐ 41 ☐ 43 ☐ 45 ☐ 47 ☐ 49 ☐ 51
 (from 17 to 32 cm foot-rest directly assembled on the frame) cm

- Frame colour** ☐ Matte black
☐ Metallic blue ☐ Pearl red ☐ Metallic grey
☐ Orange ☐ Emerald green ☐ Deep sky light blue
☐ (see "Colours" catalogue) Neon colour


- Upholstery**
☐ Tension adj. nylon backrest upholstery
☐ Tension adj. BREATH.backr.uph.
☐ Without any backrest upholstery
☐ With divided seat (joint by velcro, def.)
☐ With one entire seat (not depth adjustable)

- Upholstery colour**
 (Coloured uphol. only with Tension. adj. nylon)
☐ Black
☐ Red★ ☐ Orange★
☐ Light blue★ ☐ Green★
☐ Cornflower blue★


- ☐ **Not Detachable foot-rest**



- ☐ **Detachable foot-rest
 82° angle**
 (DP 41 cm)
 (82° footrests do not allow any 175 front castors)




- ☐ **Detachable foot-rest
 68° angle**
 (DP 41 cm)



- ☐ **Elevating foot-rest
 (detachable)**



- ☐ **Plastic separate**



- ☐ Cover f/footplates ★
☐ Foot-holding belts (W50max)
☐ Heel stops (W50max)
 (* eventually included for W 52 to 60)

- Separate aluminium
 profile tilt adjustable
 footplates:**

- ☐ forward ☐ backward
☐ Foot-holding belts (W50max)


- Single aluminium profile tilt adjustable footplate:**

(not available with elevating footrest)



- ☐ Foot-holding belts

- ☐ **Detachable Desk
 armrest h 22 cm**




- ☐ 27 cm high from the seat

Elbow-rest

- ☐ Classic (30 cm long)
☐ Straight (26 cm long)
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi modular armrest ord.form

- ☐ **Detachable "U"
 armrest h 22 cm**




- ☐ 27 cm high from the seat

Elbow-rest

- ☐ Straight (26 cm long)
☐ Straight (36 cm long)
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi modular armrest ord.form

- Height adjustable
 detachable armrest**
 (only closed)



- ☐ Desk model
☐ "U" model

Elbow-rest

- ☐ Classic (30 cm long)
☐ Classic (36 cm long)
☐ Straight (26 cm long)
☐ Straight (36 cm long)
☐ Hemiplegic RX
☐ Hemiplegic LX

note: see also Hemi modular armrest ord.form

☐ Order N° _____ ☐ Quotation
Date _____ Signature _____
Customer Ref. _____

PAGE 2/2
May 2024

RECLINING
ALTHEA.R

Dealer _____

Rear wheels ⑪

- ☐ 24" 36 spokes ☐ 12" solid*
☐ 22" 36 spokes ☐ 12" pneumatic*
☐ 20" 36 spokes (* N.A. if HP=42 or HP≥46cm if HP44: only curved rear frame)
☐ 24" MTB citybike tyre
☐ 24" MTB offroad tyre

- ☐ Pneum. Plugged (24x1.3/8") **Tyres**
☐ Plugged ☐ Smooth Pneum. high press.
☐ Solid grey 24x1.3/8"
☐ Solid KIK 24" black
☐ 24" Pneum. Marathon Plus

Pushrims ⑫

- ☐ Aluminium silver
☐ Chromium-plated steel 24"
☐ Aluminium dark
☐ Rubber coated
☐ Carbolife CURVE L 24"(*)
☐ OVAAL silver alum. (*)
☐ OVAALS dark alum. (*)
☐ OVAALG dark, w/silic. insert (*)
☐ Carbolife GEKKO 24" (*)
☐ Silicon covers 24"
(*) not available with MTB wheels

Spokeguards ⑬



- ☐ Transparent
☐ Black
☐ Fantasy
code pattern:
(see catalogue of spokeguards)

Front castors ⑭

- ☐ 100 (4"x1.1/4) solid - plastic rim
☐ 100 (4"x1.1/4) solid - alum. rim
☐ 125 (5"x1.1/4) solid - plastic rim
☐ 125 (5"x1.1/4) solid - alum. rim
☐ 150 (6") pneumatic
☐ 150 (6") solid
☐ 175 (7") solid **
☐ 175 (7") pneumatic **
(**) only if HA ≥48cm and with 68°detach.footrests

☐ STRAIGHT Rear Frame

- ☐ With small wheels for narrow passages (default) ☐ Without any small wheels for narrow passages




Unbalancing system

- ☐ Right
☐ Left
(Only with straight rear frame)

Anti-tip device ⑮


- ☐ Right
☐ Left
(Only with straight rear frame)

☐ CURVED Rear Frame Unbalancing system



- ☐ Right
☐ Left
(Only with curved rear frame)

Revolving anti-tip device




- ☐ Right
☐ Left
(Only with curved rear frame)

Single drive ⑯

(only with 24" or 22" rear wheels)

- ☐ Right
☐ Left




Push handles ⑰

- ☐ Standard ☐ Height adjustable
(max L = 48 cm)
(Compulsory with HP44cm or lower)




☒ Extended wheel plate ⑱



(The rear wheels are assembled with COG -2cm)

Lateral Supports, swing away ⑲




- ☐ Right
☐ Left

Specify the height "h"
from center of Swing Away to seat

Head-rest ⑳

Padded




- ☐ Fixed
☐ Height adjustable

Orbital

- ☐ Anatomic



- ☐ Moulded



- ☐ With lateral supports



Specify "h" & "d" where requested
Standard: h = 20 cm d = 15 cm

h = cm d = cm

Table ㉑

- ☐ Transparent
☐ RxOLx Hemiplegic transp.
☐ Plastic grey
☐ Soft padded

Specify the fastening:
☐ single ☐ double



(Only with arm-rest) OXL if L>50cm

Lined cushion ㉒

in foam polyurethane



- ☐ 3 cm high
☐ 5 cm high


Brakes ㉓

- ☐ Classic - short handle
☐ Classic - long handle
☐ Drum
☐ Right single brake
☐ Left single brake
☐ Drum+classic

Options

- 25 ☐ "M" velcro strip (hook) on seat
26 ☐ "M" velcro for VICAIR
27 ☐ "F" velcro strip (loop) on seat
28 ☐ Seat/back-rest connection flap
29 ☐ Chest harness
30 ☐ Chest belt
31 ☐ Abductor belt
32 ☐ Front protective covers
33 ☒ Stretched bar
34 ☐ Catheter holder pocket
(note: only with entire seat)

Abductor ㉔



- ☐ 1 ☐ 3 ☐ 5 ☐ 7 cm

☐ cm
Choose or specify the height from seat upholstery

- 35 ☐ R ☐ L Crutch hold./single
36 ☐ R ☐ L Crutch hold./double
37 ☐ Pump for pneumatics
38 ☐ Suitcase holder
39 ☐ 45° pelvic belt
40 ☐ 45° padded pelvic belt
41 ☐ Black backpack
42 ☐ IV bar + poles
43 ☐ IV poles

- 44 ☐ Q.rel.axles Ø12mm w/42mm bushes (def.)
45 ☐ Q.rel.a. Ø1/2" (12,7mm) w/42mm bushes
46 ☐ Q.rel.a. Ø1/2" (12,7mm) w/50mm bushes